


## System Crank 4-HR 1403 D100

Part No.: 501.10001

The system consists of 4 castors with hydraulic driven levelling feet.

Through the rotary motion of the hand crank the hydraulic oil is pressed out of the pump and flows through the hydraulic tubing into the connected levelling foot.

The system functions independently of load and the 4 castors operate completely synchronously. Each lifting castor is equipped with 3 m hydraulic tubing. The tubing can be cut to the required size and be easily connected to the pump.



Download CAD Files on [www.ergoswiss.com](http://www.ergoswiss.com)

## Application

Mobile work and transport equipment can be fitted with the lifting castors and be converted into stable working surfaces. The standard system consists of 4 lifting castors. On demand, we are also able to supply systems with up to 10 lifting castors.

## Castor

The castor with polyurethane wheels is made of injection-moulded, thermoplastic elastomer and has very low abrasion and low rolling friction.

## Technical Data

Wheel diameter	100 mm
Wheel width	32 mm
Total height	139 mm
Plate size	100x85 mm
Bearing Castor	ball - bearing
Max. system load	<b>550 kg</b>
Stroke	15 mm
Tubing length	3 m

## Packaging and Accessories

The set with 4 lifting castors will be delivered in a carton package (590 x 395 x 150 mm) containing following elements:

- 5 clamping rings
- 1 connecting screw (spare part)
- 1 magnet
- 1 tubing cutter
- 1 ring spanner
- Assembly and operating instructions

